


Intro to AWS and Boto3

INTRODUCTION TO AWS BOTO IN PYTHON



Maksim Pecherskiy
Data Engineer

What is Amazon Web Services?

Our Home



Our Data Project



What is Boto3?

```
import boto3
```

```
s3 = boto3.client('s3',  
                  region_name='us-east-1',  
                  aws_access_key_id=AWS_KEY_ID,  
                  aws_secret_access_key=AWS_SECRET)
```

```
response = s3.list_buckets()
```

AWS console

 Services ▾ Resource Groups ▾ 

 aws-demos ▾ N. Virginia ▾ Support ▾

AWS services

Find Services
You can enter names, keywords or acronyms.

▼ Recently visited services

 [AWS Cost Explorer](#)

 [Systems Manager](#)

 [AWS Cloud Map](#)

 [Billing](#)

 [EC2](#)

► All services

Build a solution

Get started with simple wizards and automated workflows.

[Launch a virtual machine](#)
With EC2

[Build a web app](#)
With Elastic Beanstalk

[Build using virtual servers](#)
With Lightsail

Access resources on the go



Access the Management Console using the AWS Console Mobile App. [Learn more](#) 


Explore AWS

Visit AWS around the world at a Summit
AWS Global Summits bring the cloud computing community together to connect, collaborate, and learn about AWS. [Learn more](#) 


Amazon SageMaker
Machine learning for every developer and data scientist. [Learn more](#) 

Amazon RDS
Set up, operate, and scale your relational database in

Creating keys with IAM.



Creating keys with IAM



AWS Management Console

AWS services

Find Services

You can enter names, keywords or acronyms.

🔍 Example: *Relational Database Service, database, RDS*

▼ Recently visited services



▶ All services

Build a solution

Get started with simple wizards and automated workflows.

Launch a virtual machine

With EC2
2-3 minutes

Build a web app

With Elastic Beanstalk
6 minutes

Build using virtual servers

With Lightsail
1-2 minutes

Access resources on the go



Access the Management Console using the AWS Console Mobile App. [Learn more](#) ↗

Explore AWS

Amazon RDS

Set up, operate, and scale your relational database in the cloud. [Learn more](#) ↗

Run Serverless Containers with AWS Fargate

AWS Fargate runs and scales your containers without having to manage servers or clusters. [Learn more](#) ↗

Amazon SageMaker

Machine learning for every developer and data scientist. [Learn more](#) ↗

Dashboard

Groups

Users

Roles

Policies

Identity providers

Account settings

Credential report

Encryption keys

Welcome to Identity and Access Management

IAM users sign-in link:

<https://320333787981.signin.aws.amazon.com/console> [Customize](#)

IAM Resources

Users: 2

Roles: 2

Groups: 0

Identity Providers: 0

Customer Managed Policies: 0

Security Status

 2 out of 5 complete.

Delete your root access keys



Activate MFA on your root account



Create individual IAM users



Use groups to assign permissions



Apply an IAM password policy



Dashboard

Groups

Users

Roles

Policies

Identity providers

Account settings

Credential report

Add user**Delete user**☐**User name ▾****Groups**☐

datacampDemoUser

None

☐

datacampUser1

None

Add user



Set user details

You can add multiple users at once with the same access type and permissions. [Learn more](#)

User name*

This field is required.

[+ Add another user](#)

Select AWS access type

Select how these users will access AWS. Access keys and autogenerated passwords are provided in the last step. [Learn more](#)

Access type*

☐

Programmatic access

Enables an **access key ID** and **secret access key** for the AWS API, CLI, SDK, and other development tools.

☐

AWS Management Console access

Enables a **password** that allows users to sign-in to the AWS Management Console.

Add user

1

2

3

4

5

▼ Set permissions



Add user to group



Copy permissions from existing user



Attach existing policies directly



Get started with groups

You haven't created any groups yet. Using groups is a best-practice way to manage users' permissions by job functions, AWS service access, or your custom permissions. Get started by creating a group. [Learn more](#)

Create group

► Set permissions boundary

User details

User name	datacampDemoUser2
AWS access type	Programmatic access - with an access key
Permissions boundary	Permissions boundary is not set

Permissions summary

The following policies will be attached to the user shown above.

Type	Name
Managed policy	AmazonS3FullAccess
Managed policy	AmazonSNSFullAccess
Managed policy	AmazonRekognitionFullAccess
Managed policy	ComprehendFullAccess

Add user



✓ Success

You successfully created the users shown below. You can view and download user security credentials. You can also email users instructions for signing in to the AWS Management Console. This is the last time these credentials will be available to download. However, you can create new credentials at any time.

Users with AWS Management Console access can sign-in at: <https://320333787981.signin.aws.amazon.com/console>

IAM User

IAM User

Key

Secret

	User	Access key ID	Secret access key
▶ ✓	datacampDemoUser2	AKIAUVFLBWNGYT2JQ7MQ	***** Show

AWS services



AWS services



AWS services



AWS services




AWS services



Sam



GetItDone



¹ [https://data.sandiego.gov/datasets/get² it³ done⁴ 311/](https://data.sandiego.gov/datasets/get%20it%3done%4311/)

Summary

- AWS Services = Home Utilities
- IAM, S3, SNS, Comprehend and Rekognition
- AWS Key / Secret
- Connecting to S3 Using Boto

```
import boto3
s3 = boto3.client('s3',
                  region_name='us-east-1',
                  aws_access_key_id=AWS_KEY_ID,
                  aws_secret_access_key=AWS_SECRET)
```


```
response = s3.list_buckets()
```

Let's harness the cloud!

INTRODUCTION TO AWS BOTO IN PYTHON

Diving into buckets

INTRODUCTION TO AWS BOTO IN PYTHON




Maksim Pecherskiy
Data Engineer

S3 Components - Buckets

- Desktop folders
- Own permission policy
- Website storage
- Generate logs



S3 Components - Objects



What can we do with buckets?

- Create Bucket
- List Buckets
- Delete Bucket



Creating a Bucket

Create boto3 client

```
import boto3
s3 = boto3.client('s3', region_name='us-east-1',
                  aws_access_key_id=AWS_KEY_ID,
                  aws_secret_access_key=AWS_SECRET)
```

Create bucket!

```
bucket = s3.create_bucket(Bucket='gid-requests')
```

Bang!



Our bucket in the console

S3 buckets

 [Discover the console](#)

Search for buckets		All access types 	
+ Create bucket		Edit public access settings	Empty
		Delete	
		6 Buckets	1 Regions 
☐ Bucket name ▾	Access  ▾	Region ▾	Date created ▾
☐  datacamp-gid-images	Objects can be public	US East (N. Virginia)	Feb 18, 2019 4:08:14 PM GMT-0800
☐  datacamp-gid-images-positive-match	Objects can be public	US East (N. Virginia)	Feb 18, 2019 4:19:51 PM GMT-0800
☐  datacamp-incoming	Objects can be public	US East (N. Virginia)	Feb 18, 2019 12:33:44 PM GMT-0800
☐  datacamp-public	Public	US East (N. Virginia)	Feb 18, 2019 12:33:19 PM GMT-0800
☐  dc-incoming	Objects can be public	US East (N. Virginia)	Feb 18, 2019 12:31:15 PM GMT-0800
☐  gid-requests	Objects can be public	US East (N. Virginia)	Apr 9, 2019 10:05:15 PM GMT-0700

Listing buckets

Create boto3 client

```
import boto3
s3 = boto3.client('s3', region_name='us-east-1',
                  aws_access_key_id=AWS_KEY_ID,
                  aws_secret_access_key=AWS_SECRET)
```

List Buckets

```
bucket_response = s3.list_buckets()
```

Listing Buckets

Get Buckets Dictionary

```
buckets = bucket_response[ 'Buckets' ]  
print(buckets)
```

Listing Buckets

```
[{'Name': 'dc-incoming',  
  'CreationDate': datetime.datetime(2019, 2, 18, 20, 31, 15, tzinfo=tzutc())},  
 {'Name': 'gid-requests',  
  'CreationDate': datetime.datetime(2019, 4, 10, 5, 5, 15, tzinfo=tzutc())}]
```


Deleting buckets

Create boto3 client

```
import boto3
s3 = boto3.client('s3', region_name='us-east-1',
                  aws_access_key_id=AWS_KEY_ID,
                  aws_secret_access_key=AWS_SECRET)
```

Delete Bucket

```
response = s3.delete_bucket('gid-requests')
```

Bye Bye Bucket



Bye Bye Bucket

S3 buckets

 [Discover the console](#)

All access types 

+ Create bucket

Edit public access settings

Empty

Delete

5 Buckets

1 Regions



☐ Bucket name ▾	Access  ▾	Region ▾	Date created ▾
☐  datacamp-gid-images	Objects can be public	US East (N. Virginia)	Feb 18, 2019 4:08:14 PM GMT-0800
☐  datacamp-gid-images-positive-match	Objects can be public	US East (N. Virginia)	Feb 18, 2019 4:19:51 PM GMT-0800
☐  datacamp-incoming	Objects can be public	US East (N. Virginia)	Feb 18, 2019 12:33:44 PM GMT-0800
☐  datacamp-public	Public	US East (N. Virginia)	Feb 18, 2019 12:33:19 PM GMT-0800
☐  dc-incoming	Objects can be public	US East (N. Virginia)	Feb 18, 2019 12:31:15 PM GMT-0800

Other operations

Client

class S3.Client

A low-level client representing Amazon Simple Storage Service (S3):

```
import boto3

client = boto3.client('s3')
```

These are the available methods:


- ***abort_multipart_upload()***
- ***can_paginate()***
- ***complete_multipart_upload()***

Summary

```
s3.create_bucket(Bucket='buck')
```

```
s3.list_buckets()
```

```
s3.delete_bucket(Bucket='buck')
```




Let's practice!

INTRODUCTION TO AWS BOTO IN PYTHON


Uploading and retrieving files

INTRODUCTION TO AWS BOTO IN PYTHON



Maksim Pecherskiy
Data engineer

Buckets and objects



A Bucket



- A bucket has a **name**
- **Name** is a string
- **Unique** name in all of S3.
- Contains **many** objects


An Object



- An object has a **key**
- **Name** is full path from bucket root
- **Unique** key in the bucket
- Can only be in **one** parent bucket


Creating the client

```
s3 = boto3.client(  
    's3',  
    region_name='us-east-1',  
    aws_access_key_id=AWS_KEY_ID,  
    aws_secret_access_key=AWS_SECRET  
)
```



Uploading files

```
s3.upload_file(  
    Filename='gid_requests_2019_01_01.csv',  
    Bucket='gid-requests',  
    Key='gid_requests_2019_01_01.csv')  
)
```



Uploading files

 Services ▾ Resource Groups ▾ 

Amazon S3 > gid-requests

Overview

Properties

Permissions

Management

 Type a prefix and press Enter to search. Press ESC to clear.

 Upload

 Create folder

Download

Actions ▾

☐	Name ▾	Last modified ▾
☐	 gid_requests_2019_01_01.csv	Apr 18, 2019 1:17:24 PM GMT-0700

Uploading more objects

Amazon S3 > gid-requests

Overview Properties Permissions

🔍 Type a prefix and press Enter to search. Press ESC to clear.

📁 Upload + Create folder Download Actions ▾

☐ Name ▾
☐ 📄 gid_requests_2018_12_30.csv
☐ 📄 gid_requests_2018_12_31.csv
☐ 📄 gid_requests_2019_01_01.csv
☐ 📄 gid_requests_2019_01_02.csv
☐ 📄 gid_requests_2019_01_03.csv

Listing objects in a bucket

```
response = s3.list_objects(  
    Bucket='gid-requests',  
    MaxKeys=2,  
    Prefix='gid_requests_2019_' )  
  
print(response)
```



Listing objects in a bucket

```
'Contents': [{ 'Key': 'gid_requests_2018_12_30.csv',  
               'LastModified': datetime.datetime(2019, 4, 18, 21, 38, 30, tzinfo=tzutc()),  
               'ETag': '"2ffc551dccadb18aba921c2d88501325"',  
               'Size': 57137,  
               'StorageClass': 'STANDARD',  
               'Owner': { 'DisplayName': 'maksim+aws-demos',  
                           'ID': '12346cf1b2f0e923b64d624ce166bb570c6dae4a2a905b419916bd365ea5a596' } },  
               { 'Key': 'gid_requests_2018_12_31.csv',  
                 'LastModified': datetime.datetime(2019, 4, 18, 21, 38, 27, tzinfo=tzutc()),  
                 'ETag': '"2ffc551dccadb18aba921c2d88501325"',
```



Listing objects in a bucket


```
'Contents': [{ 'Key': 'gid_requests_2018_12_30.csv',  
  'LastModified': datetime.datetime(2019, 4, 18, 21, 38, 30, tzinfo=tzutc()),  
  'ETag': '"2ffc551dccadb18aba921c2d88501325"',  
  'Size': 57137,  
  'StorageClass': 'STANDARD',  
  'Owner': { 'DisplayName': 'maksim+aws-demos',  
    'ID': '12346cf1b2f0e923b64d624ce166bb570c6dae4a2a905b419916bd365ea5a596' } },  
  { 'Key': 'gid_requests_2018_12_31.csv',  
    'LastModified': datetime.datetime(2019, 4, 18, 21, 38, 27, tzinfo=tzutc()),  
    'ETag': '"2ffc551dccadb18aba921c2d88501325"',
```


Listing objects in a bucket

```
'Contents': [{ 'Key': 'gid_requests_2018_12_30.csv',  
  'LastModified': datetime.datetime(2019, 4, 18, 21, 38, 30, tzinfo=tzutc()),  
  'ETag': '"2ffc551dccadb18aba921c2d88501325"',  
  'Size': 57137,  
  'StorageClass': 'STANDARD',  
  'Owner': { 'DisplayName': 'maksim+aws-demos',  
    'ID': '12346cf1b2f0e923b64d624ce166bb570c6dae4a2a905b419916bd365ea5a596' } },  
  { 'Key': 'gid_requests_2018_12_31.csv',  
    'LastModified': datetime.datetime(2019, 4, 18, 21, 38, 27, tzinfo=tzutc()),  
    'ETag': '"2ffc551dccadb18aba921c2d88501325"',
```

Getting object metadata

```
response = s3.head_object(  
    Bucket='gid-requests',  
    Key='gid_requests_2018_12_30.csv')  
  
print(response)
```




Getting object metadata

```
{ 'ResponseMetadata': { 'RequestId': '27FB1088203DD28E',  
    'HostId': '',  
    'HTTPStatusCode': 200,  
    'RetryAttempts': 0 },  
  'AcceptRanges': 'bytes',  
  'LastModified': datetime.datetime(2019, 4, 18, 21, 38, 30, tzinfo=tzutc()),  
  'ContentLength': 57137,  
  'ETag': '"2ffc551dccadb18aba921c2d88501325"',  
  'ContentType': 'binary/octet-stream',  
  'Metadata': {} }
```

Downloading files

```
s3.download_file(  
    Filename='gid_requests_downed.csv',  
    Bucket='gid-requests',  
    Key='gid_requests_2018_12_30.csv')  

```




Deleting objects

```
s3.delete_object(  
    Bucket='gid-requests',  
    Key='gid_requests_2018_12_30.csv')  
)
```



Summary

- Buckets are like folders
- Objects are like files
- `boto3.client()`
- `s3.upload_file()`
- `s3.list_objects()`
- `s3.head_object()`
- `s3.download_file()`
- `s3.delete_object()`



Let's make some objects!

INTRODUCTION TO AWS BOTO IN PYTHON